


The universal lining for many applications

REMALINE 40

Our high-quality **REMALINE** lining offers optimum surface protection for your machines and equipment. You avoid unnecessary costs for maintenance and downtime, thereby increasing the productivity of your equipment many times over.

Application areas

REMALINE 40 has been designed for a variety of wet or dry applications. In dry applications, **REMALINE 40** is frequently used for conveying coke. In wet applications, this material has proven its outstanding worth as a protective coating for sharp particles thanks to its high resistance to tearing. **REMALINE 40** also features excellent qualities for eliminating bridge formation and build-up.



Gutter lining



Typical fields of use

- Hydrocyclones
- Bucket lining for conveying wet loam/clay
- Coating for non-driven pulleys with low belt tensions (build-up protection)
- Flexilo and bunker lining

Advantages

- Protection against damage caused by sharp material
- Universal applications
- Easy and fast installation
- Technical consultation and data available anytime
- ▶ **Increases the efficiency of your equipment**

The universal lining for many applications

REMALINE 40



Industrie

Technical properties

Product characteristics	REMALINE 40 is a rubber material based on natural rubber offering universal applications.	
	CN bonding layer: REMALINE 40 comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.	
Storage stability	Max. 24 months ▶ At 25 °C ± 2 °C with no loss in quality. Subject to DIN regulation 7716.	
Color		black, white
Polymer	DIN ISO 1629	NR
Specific weight	DIN EN ISO 1183	1,05 g/cm ³
Hardness	ISO 868-2003 (DIN 53505)	48 ± 5 Shore A
Abrasion	DIN ISO 4649-2006	140 mm ³
Resilience elasticity	ISO 4462-1986 (DIN 53512)	63 %
Available sizes*	Standard thickness in mm	3 - 20
	Standard width in mm	1 500 or 2 000
Special qualities	<ul style="list-style-type: none">▶ Oil- and grease-resistant▶ Highly flame-retardant (REMALINE 40 „S“)▶ Heat-resistant (REMALINE 40 HR)▶ Certified food-safe (FDA, Cat. 3 + 4 of BGVV)	

*Other dimensions available on request.

REMALINE 40 is also available with fabric reinforcement.

REMA TIP TOP GmbH
Business Unit Industrie

Gruber Strasse 63
Phone:
Fax:
www.rema-tiptop.com

85586 Poing/Germany
+49 8121 707-234
+49 8121 707-222
info@tiptop.de

Your local contact:

582 1081 - II.07 Printed in Germany

